



Europe based
aftersale service
Company HQ in Spain



BXB 5-30KHV

High Voltage

LiFePO4 BATTERY



Support black start



IP65 outdoor and indoor application



Quick stackable plug-in design



Parallel capacity up to 10 clusters



Support low temperature charging and discharging



Reliable battery cells and BMS control



+34 985 194 232

CALLE COVADONGA 5, 33002 (OVIEDO, ASTURIAS)

www.bexiegroup.com

BEXIE GROUP designs, manufactures and delivers high-performance solar electric technology worldwide. Our high-efficiency solar cells enable us to produce different types of solar panels with highest efficiency.

BXB 5-30KHV

LiFePO4 BATTERY

Electrical Characteristics						
Model	BXB 5KHV	BXB 10KHV	BXB 15KHV	BXB20KHV	BXB 25KHV	BXB 30KHV
Battery Module Quantity	1	2	3	4	5	6
Total Capacity	50 Ah					
Nominal Voltage	102.4 V	204.8 V	307.2 V	409.6 V	512 V	614.4 V
Size, W*D*H mm, inches	560*400*503, 22.0*15.7*19.8	560*400*735, 22.0*15.7*28.9	560*400*967, 22.0*15.7*38.1	560*400*1199, 22.0*15.7*47.2	560*400*1431, 22.0*15.7*56.3	560*400*1663, 22.0*15.7*65.5
Total Energy	5.1 kWh	10.2 kWh	15.3 kWh	20.4 kWh	25.6 kWh	30.7 kWh
Rated Charge/ Discharge Current	30 A, 0.6C					
Weight	89.2 kg, 196.7 lbs	148.1 kg, 196.7 lbs	207.6 kg, 457.7 lbs	266.8 kg, 588.2 lbs	326 kg, 718.7 lbs	385.2 kg, 849.2 lbs
Design Cycle Life	6000, 0.5C at 25 °C, 80% DOD, 80% SOH					
Operating Temperature	Charging Temperature: -5 °C~55 °C/5 °F~131 °F Discharge Temperature: -15 °C~55 °C/5 °F~131 °F					
Storage Temperature	-15 °C~55 °C, 5 °F~131 °F					
Self-Discharge Rate of Module	≤2% per month, at 25 °C/77 °F					
Max. Parallel Capacity	307 kWh					
Ingress Protection	IP55, in stacked up state					
Certificates & Standards	IEC 62619/EN 61000-6-1 & EN 61000-6-3/UN38.3/RoHS, REACH					

Specifications are subject to change without advanced noticed.

[1*] Recommended operating temperature: 10~30 °C/50 °F~86 °F.

[2*] Recommended storage temperature: 10~30 °C/50 °F~86 °F